

Leiyang BTL New Materials Co., Ltd.

Room 706, No. 154, Wuyi East Road, Niezhou Residential Committee, Caizichi Sub-district Office,
Leiyang City, Hengyang City, Hunan Province, China
TEL:86-182-73793022 FAX:86-182-73793022 EMAIL:lixifirm@outlook.com

=====

SAFETY DATA SHEET

SECTION 1. IDENTIFICATION

Product Identifier: Manganese Dioxide

Product Code: MN-OX2-02

CAS Number: 1313-13-9

Relevant identified uses of the substance: Scientific research and development

Supplier details:

Leiyang BTL New Materials Co., Ltd.

ADD:Room 706, No. 154, Wuyi East Road, Niezhou Residential Committee, Caizichi Sub-district Office, Leiyang City, Hengyang City, Hunan Province, China

T:+86-182-73793022

F:+86-182-73793022

Emergency telephone number:

+8618273793022

SECTION 2. HAZARDS IDENTIFICATION

Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

GHS07

Acute Tox. 4 H302 Harmful if swallowed.

Acute Tox. 4 H332 Harmful if inhaled.

Classification according to Directive 67/548/EEC or Directive 1999/45/EC

Xn; Harmful

R20/22: Harmful by inhalation and if swallowed.

Information concerning particular hazards for human and environment:

N/A

Hazards not otherwise classified

No data available

Label elements

Labelling according to Regulation (EC) No 1272/2008

The substance is classified and labeled according to the CLP regulation.

Hazard pictograms



GHS07

Leiyang BTL New Materials Co., Ltd.

Room 706, No. 154, Wuyi East Road, Niezhou Residential Committee, Caizichi Sub-district Office,
Leiyang City, Hengyang City, Hunan Province, China
TEL:86-182-73793022 FAX:86-182-73793022 EMAIL:lixifirm@outlook.com

=====

Signal word: Warning

Hazard statements

H302+H332 Harmful if swallowed or if inhaled.

Precautionary statements

P261 Avoid breathing dust/fume/gas/mist/vapors/spray.

P264 Wash thoroughly after handling.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P301+P312 IF SWALLOWED: Call a POISON CENTER/doctor/.../if you feel unwell.

P312 Call a POISON CENTER/doctor/.../if you feel unwell.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

WHMIS classification

Not controlled

Classification system

HMIS ratings (scale 0-4)

(Hazardous Materials Identification System)

HEALTH

FIRE

REACTIVITY

2

0

1

Health (acute effects) = 2

Flammability = 0

Physical Hazard = 1

Other hazards

Results of PBT and vPvB assessment

PBT: N/A

vPvB: N/A

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substances

CAS No. / Substance Name:

1313-13-9 Manganese(IV) oxide

Identification number(s):

EC number: 215-202-6

Index number: 025-001-00-3

SECTION 4. FIRST AID MEASURES

Description of first aid measures

If inhaled:

Supply patient with fresh air. If not breathing, provide artificial respiration. Keep patient warm.

Seek immediate medical advice.

In case of skin contact:

Immediately wash with soap and water; rinse thoroughly.

Seek immediate medical advice.

In case of eye contact:

Rinse opened eye for several minutes under running water. Consult a physician.

If swallowed:

Leiyang BTL New Materials Co., Ltd.

Room 706, No. 154, Wuyi East Road, Niezhou Residential Committee, Caizichi Sub-district Office,
Leiyang City, Hengyang City, Hunan Province, China
TEL:86-182-73793022 FAX:86-182-73793022 EMAIL:lixifirm@outlook.com

Seek medical treatment.

Information for doctor

Most important symptoms and effects, both acute and delayed

No data available

Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5. FIREFIGHTING MEASURES

Extinguishing media

Suitable extinguishing agents

Product is not flammable. Use fire-fighting measures that suit the surrounding fire.

Special hazards arising from the substance or mixture

If this product is involved in a fire, the following can be released:

Advice for firefighters

Protective equipment:

Wear self-contained respirator.

Wear fully protective impervious suit.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Use personal protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

Environmental precautions:

Do not allow product to enter drains, sewage systems, or other water courses.

Do not allow material to penetrate the ground or soil.

Methods and materials for containment and cleanup:

Dispose of contaminated material as waste according to section 13.

Ensure adequate ventilation.

Prevention of secondary hazards:

No special measures required.

Reference to other sections

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7. HANDLING AND STORAGE

Handling

Precautions for safe handling

Keep container tightly sealed.

Store in cool, dry place in tightly closed containers.

Ensure good ventilation at the workplace.

Information about protection against explosions and fires:

The product is not flammable

Conditions for safe storage, including any incompatibilities

Requirements to be met by storerooms and receptacles:

No special requirements.

Information about storage in one common storage facility:

Leiyang BTL New Materials Co., Ltd.

Room 706, No. 154, Wuyi East Road, Niezhou Residential Committee, Caizichi Sub-district Office,
Leiyang City, Hengyang City, Hunan Province, China
TEL:86-182-73793022 FAX:86-182-73793022 EMAIL:lixifirm@outlook.com

Store away from oxidizing agents.
Further information about storage conditions:
Keep container tightly sealed.
Store in cool, dry conditions in well-sealed containers.
Specific end use(s)
No data available

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Additional information about design of technical systems:
Properly operating chemical fume hood designed for hazardous chemicals and having an average face velocity of at least 100 feet per minute.
Control parameters
Components with limit values that require monitoring at the workplace:
1313-13-9 Manganese(IV) oxide (100.0%)

PEL (USA) Ceiling limit value: 5 mg/m³ as Mn

REL (USA) Short-term value: 3 mg/m³

Long-term value: 1 mg/m³ as Mn

TLV (USA) Long-term value: 0.02* 0.1* mg/m³ as Mn; *respirable **inhalable fraction

EL (Canada) Long-term value: 0.2 mg/m³ as Mn; R

Additional information: No data

Exposure controls

Personal protective equipment

Follow typical protective and hygienic practices for handling chemicals.

Keep away from foodstuffs, beverages and feed.

Remove all soiled and contaminated clothing immediately.

Wash hands before breaks and at the end of work.

Maintain an ergonomically appropriate working environment.

Breathing equipment:

Use suitable respirator when high concentrations are present.

Recommended filter device for short term use:

Use a respirator with type N95 (USA) or PE (EN 143) cartridges as a backup to engineering controls.

Risk assessment should be performed to determine if air-purifying respirators are appropriate. Only use equipment tested and approved under appropriate government standards.

Protection of hands: Impervious gloves

Inspect gloves prior to use.

Suitability of gloves should be determined both by material and quality, the latter of which may vary by manufacturer.

Material of gloves

Nitrile rubber, NBR

Penetration time of glove material (in minutes)

480

Glove thickness

0.11 mm

Eye protection: Safety glasses

Body protection: Protective work clothing.

Leiyang BTL New Materials Co., Ltd.

Room 706, No. 154, Wuyi East Road, Niezhou Residential Committee, Caizichi Sub-district Office,
Leiyang City, Hengyang City, Hunan Province, China
TEL:86-182-73793022 FAX:86-182-73793022 EMAIL:lixifirm@outlook.com

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Appearance:

Form: Powder or solid in various forms

Color: Black

Odor: No data available

Odor threshold: No data available.

pH: N/A

Melting point/Melting range: 535 °C (995 °F) (dec)

Boiling point/Boiling range: No data available

Sublimation temperature / start: No data available

Flammability (solid, gas): No data available.

Ignition temperature: No data available

Decomposition temperature: No data available

Autoignition: No data available.

Danger of explosion: No data available.

Explosion limits:

Lower: No data available

Upper: No data available

Vapor pressure: N/A

Density at 20 °C (68 °F): 5.026 g/cm³ (41.942 lbs/gal)

Relative density: No data available.

Vapor density: N/A

Evaporation rate: N/A

Solubility in Water (H₂O): No data available

Partition coefficient (n-octanol/water): No data available.

Viscosity:

Dynamic: N/A

Kinematic: N/A

Other information

No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity

No data available

Chemical stability

Stable under recommended storage conditions.

Thermal decomposition / conditions to be avoided:

Decomposition will not occur if used and stored according to specifications.

Possibility of hazardous reactions

Reacts with strong oxidizing agents

Conditions to avoid

No data available

Incompatible materials:

Oxidizing agents

SECTION 11. TOXICOLOGICAL INFORMATION

Information on toxicological effects

Leiyang BTL New Materials Co., Ltd.

Room 706, No. 154, Wuyi East Road, Niezhou Residential Committee, Caizichi Sub-district Office,
Leiyang City, Hengyang City, Hunan Province, China
TEL:86-182-73793022 FAX:86-182-73793022 EMAIL:lixifirm@outlook.com

Acute toxicity:

Harmful if inhaled.

Harmful if swallowed.

The Registry of Toxic Effects of Chemical Substances (RTECS) contains acute toxicity data for this substance.

LD/LC50 values that are relevant for classification: Oral LD50 3478 mg/kg (rat)

Skin irritation or corrosion: May cause irritation

Eye irritation or corrosion: May cause irritation

Sensitization: No sensitizing effects known.

Germ cell mutagenicity: No effects known.

Carcinogenicity:

No classification data on carcinogenic properties of this material is available from the EPA, IARC, NTP, OSHA or ACGIH.

Reproductive toxicity:

The Registry of Toxic Effects of Chemical Substances (RTECS) contains reproductive data for this substance.

Specific target organ system toxicity - repeated exposure: No effects known.

Specific target organ system toxicity - single exposure: No effects known.

Aspiration hazard: No effects known.

Subacute to chronic toxicity:

The Registry of Toxic Effects of Chemical Substances (RTECS) contains multiple dose toxicity data for this substance.

Additional toxicological information:

To the best of our knowledge the acute and chronic toxicity of this substance is not fully known.

SECTION 12. ECOLOGICAL INFORMATION

Toxicity

Aquatic toxicity:

No data available

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

Additional ecological information:

Do not allow undiluted product or large quantities to reach groundwater, water courses, or sewage systems.

Avoid transfer into the environment.

Results of PBT and vPvB assessment

PBT: N/A

vPvB: N/A

Other adverse effects

No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Recommendation

Consult official regulations to ensure proper disposal.

Leiyang BTL New Materials Co., Ltd.

Room 706, No. 154, Wuyi East Road, Niezhou Residential Committee, Caizichi Sub-district Office,
Leiyang City, Hengyang City, Hunan Province, China
TEL:86-182-73793022 FAX:86-182-73793022 EMAIL:lixifirm@outlook.com

=====

Uncleaned packagings:
Recommendation:
Disposal must be made according to official regulations

SECTION 14. TRANSPORT INFORMATION

UN-Number
DOT, ADN, IMDG, IATA
N/A
UN proper shipping name
DOT, ADN, IMDG, IATA
N/A
Transport hazard class(es)
DOT, ADR, ADN, IMDG, IATA
Class
N/A
Packing group
DOT, IMDG, IATA
N/A
Environmental hazards:
N/A
Special precautions for user
N/A
Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code
N/A
Transport/Additional information:
DOT
Marine Pollutant (DOT):
No

SECTION 15. REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture
National regulations
All components of this product are listed in the U.S. Environmental Protection Agency Toxic
Substances Control Act Chemical substance Inventory.
All components of this product are listed on the Canadian Domestic Substances List (DSL).
SARA Section 313 (specific toxic chemical listings)
1313-13-9 Manganese(IV) oxide
California Proposition 65
Prop 65 - Chemicals known to cause cancer
Substance is not listed.
Prop 65 - Developmental toxicity
Substance is not listed.
Prop 65 - Developmental toxicity, female
Substance is not listed.
Prop 65 - Developmental toxicity, male
Substance is not listed.
Information about limitation of use:
For use only by technically qualified individuals.
Other regulations, limitations and prohibitive regulations

Leiyang BTL New Materials Co., Ltd.

Room 706, No. 154, Wuyi East Road, Niezhou Residential Committee, Caizichi Sub-district Office,
Leiyang City, Hengyang City, Hunan Province, China
TEL:86-182-73793022 FAX:86-182-73793022 EMAIL:lixifirm@outlook.com

=====

Substance of Very High Concern (SVHC) according to the REACH Regulations (EC) No. 1907/2006.

Substance is not listed.

The conditions of restrictions according to Article 67 and Annex XVII of the Regulation (EC) No 1907/2006 (REACH) for the manufacturing, placing on the market and use must be observed.

Substance is not listed.

Annex XIV of the REACH Regulations (requiring Authorisation for use)

Substance is not listed.

REACH - Pre-registered substances

Substance is listed.

Chemical safety assessment:

A Chemical Safety Assessment has not been carried out.

16. OTHER INFORMATION

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH). The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. Anhui Fitech Material Co.,Ltd shall not be held liable for any damage resulting from handling or from contact with the above product. See reverse side of invoice or packing slip for additional terms and conditions of sale.